# Sew Sweetness Selvage Zipper Pouch

Use your selvages and make a pretty zippered pouch! This pouch has darts, which give it a great 3-dimensional look!

All pattern pieces include the seam allowance.

Finished Size: 10-1/2" long x 5-1/2" tall x 2" deep

**All cutting measurements given throughout the pattern are** *width x height*.

### **SUPPLIES**

- fat quarter of lining fabric
- various selvages (I'll show you how to cut your selvages in the video!)
- 1/3 yard of Pellon SF-101 Shape Flex fusible woven interfacing
- 12" x 14" of foam interfacing (By Annie's Soft and Stable, Pellon Flex Foam, Bosal In-R-Form, or automotive head-
- 12" all-purpose (#3 dress/skirt) zipper

### NOTIONS

- Clover Wonder Clips or pins
- Zipper foot
- Pressing cloth
- **Rotary Cutter and Cutting Mat**
- Scissors
- Disappearing Ink Fabric Marker
- Optional: denim needle, for sewing the bag layers together, if needed.
- Optional: Walking foot for sewing the Soft and Stable layers together, if needed.

### **CUTTING INSTRUCTIONS**

Please cut your fabric pieces in the order listed, so that you will have plenty of fabric for the bag. When printing pattern pieces, always make sure your printer is set to scaling at 'none' or 'actual size' so pieces print at correct size. Measure the tester 1" or 4cm square to make sure that your pattern pieces printed at the correct size.

Cut each from Lining Fabric and Shape Flex:  (2) Main Panel, using the Main Panel pattern piece, cut on the fold
Cut each from foam interfacing: (2) 12" x 7"
Cut each from exterior fabric: (2) Zipper Tab, 3" x 1-1/2"

## ATTACH THE INTERFACING

Place the fusible (tacky) side of the Shape Flex against the wrong side of the Lining Main Panel. Fuse according to 1. manufacturer instructions. Repeat for the remaining Lining Main Panel.

Helpful Hint: To fuse Shape Flex, first place the Lining Main Panel face down, followed by the interfacing (tacky side down), then my pressing cloth. I lightly spritz the pressing cloth with water, then iron, overlapping each area, for approximately 10 seconds on each spot. When finished, it should be firmly attached to your fabric.

Watch the free video at www.youtube.com/sewsweetness

Need help?? E-mail me any time at sara@sewsweetness.com

Please add your finished bag to my group! https://www.facebook.com/groups/sewsweetnessfans/

or tag your finished bag on Instagram or Twitter using hashtag #selvagezipperpouch and #sewsweetnesspattern

Copyright ©Sew Sweetness 2017

http://www.sewsweetness.com

Please check out my site for free tutorials on bags and bag-making techniques!

4cm

1" square



Main Panel pattern piece

Cut 2 exterior fabric

Cut 2 lining fabric

Cut 2 foam interfacing

Cut 2 Shape Flex

Place on the Fold

